THE EPOXYLITE CORPORATION -- EPOXYLITE #810 PART A -- 1560-00-066-7840

Product ID:EPOXYLITE #810 PART A

MSDS Date:06/09/2000

FSC:1560

NIIN:00-066-7840 Status Code:A

Kit Part:Y

MSDS Number: CKSGM === Responsible Party ===

Company Name: THE EPOXYLITE CORPORATION

Address:9400 TOLEDO WAY

Box:19671 City:IRVINE State:CA

ZIP:92713-9671

Country:US

Info Phone Num:714-951-3231

Emergency Phone Num:(800)424-9300

Resp. Party Other MSDS Num

.:J-1

Chemtrec Ind/Phone:(800)424-9300

CAGE:11147

=== Contractor Identification ===

Company Name: THE EPOXYLITE CORPORATION

Address:9400 TOLEDO WAY

Box:19671 City:IRVINE State:CA

ZIP:92713-9671 Country:US

Phone:714-951-3231

CAGE:11147

======= Composition/Information on Ingredients ========

Ingred Name: POLYGLYCIDYL ETHER PHENOL-FORMALDEHYDE NOVALAC OR PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER

CAS:28064-14-4 Minumum % Wt:30. Maxumum % Wt:40.

Ingred Name:4-VINYL-1-CYCLOHE

XENE DIEPOXIDE CAS:106-87-6 RTECS #:RN8640000 Minumum % Wt:15. Maxumum % Wt:20. ACGIH TLV:57 MG/M3;10 PPM

============ Hazards Identification =========================

LD50 LC50 Mixture:NONE STATED FOR PRODUCT AS A WHOLE
Health Hazards Acute and Chronic:EYE: MAY CAUSE MILD TRANSIENT
IRRITATION. NO CORNEAL INJURY LIKELY. SKIN: MAY CAUSE MINOR
IRRITATION. MAY CAUSE SKIN SENSITIZATION. NOT LIKELY TO BE ABSORBED
IN TOXIC AMOUNTS. INGESTION: LOW IN TOXICI TY. INHALATION:
RESP

IRATORY TRACT IRRITATION NOT LIKELY.

Explanation of Carcinogenicity:NO DATA PROVIDED BY RESPONSIBLE PARTY.

Effects of Overexposure: EYES: MINOR TRANSIENT IRRITATION.

Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN ALLERGIES, SKIN DISORDERS, EYE DISORDERS.

First Aid:EYE CONTACT: FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUUTES. GET MEDICAL ATTENTION! SKIN CONTACT: PROMPTLY WASH WITH SOAP AND WATER. ING

STION: SEEK MEDCIAL ASSISTANCE IMMEDIATELY.


INHALATION: REMOVE PERSON TO FRESH AIR. SEEK MEDICAL ATTENTION IF NEEDED.

============ Fire Fighting Measures =========================

Flash Point Method:PMCC Flash Point:>93.3C, 200.F

Lower Limits:N/D Upper Limits:N/D

Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL, WATER SPRAY. Fire Fighting Procedures:WATER SHOULD BE USED TO KEEP FIRE EXPOSED CONTAINERS COOL. IF A LEAK OR SPILL HAS NOT IGNITED, USE WATER SPRAY TO DI



HCC:V5

Boiling Pt:>20

0.C, 392.F B.P. Text:760 MM HG Decomp Temp:>200.C, 392.F Decomp Text:760 MM HG Spec Gravity:1.6 Solubility in Water: