

CENTURY LUBRICANTS CO -- HIGH VACUUM GREASE -- 9150-00-965-2408

=====
Product Identification
=====

Product ID:HIGH VACUUM GREASE

MSDS Date:07/25/1996

FSC:9150

NIIN:00-965-2408

MSDS Number: CKVBZ

=== Responsible Party ===

Company Name:CENTURY LUBRICANTS CO

Address:2140 S 88TH STREET

City:KANSAS CITY

State:MO

ZIP:66111-8701

Country:US

Info Phone Num:800-800-6457

Emergency Phone Num:(800)424-9300

Re

sp. Party Other MSDS Num.:HPC11 188078-AA

Preparer's Name:M.D. HART

Chemtec Ind/Phone:(800)424-9300

CAGE:12905

=== Contractor Identification ===

Company Name:CENTURY LUBRICANTS CO

Address:2140 S 88TH STREET

Box:City:KANSAS CITY

State:MO

ZIP:66111-8701

Country:US

Phone:913-422-4022/ 800-800-6457

CAGE:12905

Company Name:IBIDE INTL CORP

Address:2804 LINDIN WAY (FORM:229 GENTLEBROOK RD

Box:City:WOODSTOCK (FORM:OWINGS MILLS

State:MD

ZIP:21163-1400

Country:US

Phone:410-521-8711

Contract Num:SP0450-00

-W-2106
CAGE:06PW2
Company Name:OMEGA ELECTRONICS
Address:95 HARTFORD AVE
Box:City:SAN CARLOS
State:CA
ZIP:94070
Country:US
Phone:650-591-2510
Contract Num:SP0450-01-M-C895
CAGE:7W657

=====
Composition/Information on Ingredients
=====

Ingred Name:SILICA THICKNER
OSHA PEL:20 MPPCF AS DUST

=====
Hazards Identification
=====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: NONE EXPECTED. SKIN: PROLONGED
GED

OR REPEATED CONTACT MAY CAUSE MILD IRRITATION. INHALATION: NONE
EXPECTED. INGESTION: NONE EXPECTED. CHRONIC: NONE EXPECTED.

Explanation of Carcinogenicity:NOT LISTED.

Effects of Overexposure:EYES: NONE EXPECTED. SKIN: PROLONGED OR
REPEATED CONTACT MAY CAUSE MILD IRRITATION. INHALATION: NONE
EXPECTED. INGESTION: NONE EXPECTED. CHRONIC: NONE EXPECTED.

Medical Cond Aggravated by Exposure:NOT PROVIDED

=====
First Aid Measures
=====

First Ai

d:EYES: FLUSH WITH WATER. SEE PHYSICIAN. SKIN: WASH WITH SOAP
AND WATER. IF HIGH PRESSURE, GET IMMEDIATE MEDICAL ATTENTION.
INHALATION: REMOVE FROM CONTAMINATED AREA.

=====
Fire Fighting Measures
=====

Flash Point Method:COC

Flash Point:=148.9C, 300.F

Lower Limits:UNK

Upper Limits:UNK

Extinguishing Media:DRY CHEMICAL, CO2, WATERSPRAY, FOAM.

Fire Fighting Procedures:AVOID BREATHING VAPORS. USE BREATHING
APPARATUS IN CONFINED AREAS. COOL EXPOSED C

CONTAINERS WITH
WATERSPRAY.

===== Accidental Release Measures =====

Spill Release Procedures:ADD ABSORBENT TO SPILL AREA. KEEP SILICONE PRODUCTS OUT OF SEWERS AND WATERWAYS. ADVISE AUTHORITIES IF THE DO ENTER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT HANDLE NEAR HEAT, FLAMES, SPARKS. DO NOT WELD OR HEAT EMPTY CONTAINERS.

Other Precautions:NOT PROVIDED

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY NEEDED.

Ventilation:GENERAL ADEQUATE. USE LOCAL MECHANICAL TO INSURE TLV'S NOT SURPASSED WHERE APPLICABLE.

Protective Gloves:CHEMICALLY RESISTANT DESIRABLE.

Eye Protection:GOGGLES OR FACESHIELD DESIRABLE.

Other Protective Equipment:NONE NORMALLY NEEDED.

Work Hygienic Practices:NOT PROVIDED

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:>315.6C, 600.F

Melt/Freeze Pt:M.P/F.P Text:N.A.

Decomp Temp:Decomp Text:NONE PROVIDED BY MFR

Vapor Pres:NIL

Vapor Density:>1(AIR=1)

Spec Gravity:0.97 (WATER)

pH:NONE PROVIDED

Viscosity:NONE PROVIDED BY MFR

Evaporation Rate & Reference: