View NSN Online: https://aerobasegroup.gr/nsn/7510-00-161-4236

Product ID:STAMP PAD INK CID: A-A-209B MSDS Date:03/26/1997 FSC:7510 NIIN:00-161-4236 Status Code:A MSDS Number: CLBXG === Responsible Party === Company Name: AMERICAN WRITING INK CO. INC. Address:33 ENDICOTT STREET City:NORWOOD State:MA ZIP:02062-3006 Country:US Info Phone Num:617-76 2-0026 Emergency Phone Num:617-482-9167 Preparer's Name: H LEVINSON CAGE:82956 === Contractor Identification === Company Name: AMERICAN INK AND OIL CORP Address:33 ENDICOTT STREET Box:City:NORWOOD State:MA ZIP:02062-3006 Country:US Phone:781-762-0026 / FAX: 781-762-1617 Contract Num:GS-14F-64041 CAGE:82956

Ingred Name:NO HAZARDOUS INGREDIENTS

Reports of Carc

 inogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE: IRRITATION, TEARING, REDNESS.
SKIN: IRRITATION. PROLONGED/REPEATED EXPOSURE CAUSES REDNESS, DRINESS, CRACKING OF SKIN. INHAL: BREATHING HIGH CONCENTRATIONS OF VAPORS/MISTS CAUSES IRRITATION OF NO SE/THROAT. INGEST: IRRITATION OF DIGESTIVE TRACT.
Medical Cond Aggravated by Exposure:PRE-EXISTING EYE/SKIN/RESPIRATORY DISORDERS, OR PRE-EXISTING IMPAIRED PERIPHERAL NERVE FUNCTION MAY BE AGGRIVATED BY E
XPOSURE TO INK.

First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES, LIFTING LIDS TO RINSE ENTIRE EYE. WASH W/ANTI-IRRITATING SOAP, SUCH AS BABY SOAP. CALL DR IMMED. SKIN: FLUSH W/COPIOUS AMOUNTS OF WATER FOR 15 MINS, USING MILD S OAP. REMOVE CONTAMINATED CLOTHING IMMEDIATELY. CALL DR. INHALATION: NO ADVERSE EFFECTS EXPECTED. INGESTION: INDUCE VOMITING. CALL DR.

=================== Fire Fighting Measures

Flash Point Method:TCC Flash Point:=182.2C, 360.F Extinguishing Media:CO2, DRY CHEMICAL FOR SMALL FIRES. ALCOHOL TYPE FOAM OR WATER SPRAY FOR LARGE FIRES. Fire Fighting Procedures:NONE Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures: CONTAIN SPILL. PREVENT CONTAMINATION OF GROUND AND SURFACE WATERS. REMOVE SPILLED INK WITH ABSORBANTS SUCH AS SAWDUST/VERMICULITE.

Handling and Storage Precautions: KEEP CONTAINERS TIGHTLY CLOSED AND ON END TO PREVENT SEAPAGE.

Respiratory Protection:NOT NORMALLY NEEDED Ventilation:ADEQUATE AIR CIRCULATION NORMALLY SUFFICIENT Protective Gloves:IMPERVIOUS Eye Protection:APPROVED EYE PROTECTION TO PREVENT EYE CONTACT Other Protective Equipment:SOURCE OF CLEAN WATER IN WORK AREA FOR FLUSHING EYES AND S

KIN.

Work Hygienic Practices: WASH WITH SOAP AND WATER IF SPLASHING OCCURS. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. Supplemental Safety and Health

Boiling Pt:>121.1C, 250.F Vapor Pres: