View NSN Online: https://aerobasegroup.gr/nsn/6750-01-050-7789

EASTMAN KODAK COMPANY -- 192 7698, PT A, KODAK FLEXICOLOR DEVELOPER 6750-01-050-7789

============= Product Identification ========================

Product ID:192 7698, PT A, KODAK FLEXICOLOR DEVELOPER

MSDS Date:07/26/2000

FSC:6750

NIIN:01-050-7789 Status Code:A

Kit Part:Y

MSDS Number: CLDMY === Responsible Party ===

Company Name: EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY ZIP:14650 Country:US

ı

nfo Phone Num:716-477-3194 MSDS:800-242-2424

Emergency Phone Num:716-722-5151 Preparer's Name:NOT PROVIDED

CAGE:19139

=== Contractor Identification ===

Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST Box:City:ROCHESTER

State:NY

ZIP:14650-1115 Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

======= Composition/Information on Ingredients ========

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Minumum % Wt:55. Maxumum % Wt:60. Other REC Li mits:NOT PROVIDED

Code:F

Ingred Name: POTASSIUM CARBONATE

CAS:584-08-7

RTECS #:TS7750000 Minumum % Wt:25. Maxumum % Wt:30.

Other REC Limits:NOT PROVIDED

OSHA PEL:NOT PROVIDED ACGIH TLV:NOT PROVIDED

Ingred Name: POTASSIUM BICARBONATE

CAS:298-14-6 Minumum % Wt:5. Maxumum % Wt:10. Other REC Limits:NOT PROVIDED OSHA PEL:NOT PROVIDED

Ingred Name:SODIUM SULFITE

ACGIH TLV:NOT PROVIDED

CAS:7757-83-7

RTECS #:WE2150000

Minumum % Wt:1. Maxumum % Wt:5.

Other REC Limits:NOT PROVIDED

OSHA PEL:NOT PROV

IDED

ACGIH TLV:NOT PROVIDED

Ingred Name: PENTETIC ACID, PENTASODIUM SALT

CAS:140-01-2 Minumum % Wt:1. Maxumum % Wt:5.

Other REC Limits:NOT PROVIDED

OSHA PEL:NOT PROVIDED ACGIH TLV:NOT PROVIDED

Ingred Name:POTASSIUM SULFITE

CAS:10117-38-1 RTECS #:WT3530000 Minumum % Wt:1.

Maxumum % Wt:5.

Other REC Limits:NOT PROVIDED

OSHA PEL:NOT PROVIDED ACGIH TLV:NOT PROVIDED

Ingred Name:SODIUM BROMIDE

CAS:7647-15-6 RTECS #:VZ3150000

Minumum % Wt:1.

Maxumum % Wt:5.

Other REC Limits:NOT PROVIDED

OSHA PEL:NOT P

ROVIDED ACGIH TLV:NOT PROVIDED

========== Hazards Identification ================

LD50 LC50 Mixture: NOT PROVIDED

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: EXPECTED TO BE A LOW HAZARD FOR USUAL INDUSTRIAL OR COMMERCIAL HANDLING BY TRAINED PERSONNEL. IN CONTACT WITH STRONG ACIDS OR IF HEATED, SULFITES MAY LIBERATE SULFUR DIOXIDE GAS. SULFUR D IOXIDE GAS IS IRRITATING TO THE RESPIRATORY TRACT. SOME ASTHMATI

CS OR HYPERSENSITIVE

INDIVIDUALS MAY EXPERIENCE DIFFICULT BREATHING. EYES: NO SPECIFIC HAZARD KNOWN. MAY CAUSE TRANSIENT IRRITATION. SKI N: THIS MATERIAL HAS A LOW POTENTIAL TO CAUSE ALLERGIC SKIN REACTIONS; HOWEVER, CASES OF HUMAN SKIN SENSITIZATION HAVE BEEN REPORTED. INGESTION: MAY BE HARMFUL IF SWALLOWED.

Explanation of Carcinogenicity:INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC): NONE - AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS (ACGIH): SODI

UM BISULFITE, A4, NOT

CLASSIFIABLE AS A HUMAN CARCINOGEN; SULFUR DIOXI DE, A4, NOT CLASSIFIABLE AS A HUMAN CARCINOGEN. - NATIONAL TOXICOLOGY PROGRAM (NTP): NONE - OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA): NONE

Effects of Overexposure:INHALATION: IN CONTACT WITH STRONG ACIDS OR IF HEATED, SULFITES MAY LIBERATE SULFUR DIOXIDE GAS. SULFUR DIOXIDE GAS IS IRRITATING TO THE RESPIRATORY TRACT. SOME ASTHMATICS OR HYPERSENSITIVE INDIVIDUAL S MAY EXPERIENCE DIFFICUL

T BREATHING.

EYES: MAY CAUSE TRANSIENT IRRITATION.

Medical Cond Aggravated by Exposure:SOME ASTHMATICS, HYPERSENSITIVE OR SULFITE-SENSITIVE INDIVIDUALS MAY EXPERIENCE DIFFICULT BREATHING, WHEEZING, CHEST TIGHTNESS, STOMACH UPSET, HIVES, FAINTNESS, WEAKNESS AND DIARRHEA.

First Aid:INHALATION: IF SYMPTOMATIC, MOVE TO FRESH AIR. TREAT SYMPTOMATICALLY. GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EYES: ANY M

ATERIAL THAT CONTACTS THE EYE SHOULD BE WASHED OUT IMMEDIATELY WITH WATER. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. SKIN: WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. INGESTION: DRINK 1-2 GLASSES OF WATER. SEEK MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

========== Fire Fighting Measures ================

Flash Point: NONFLAMMABLE

Extinguishing Media: USE APPROPRIATE AGENT FOR ADJACENT FIRE.

Fire Fighting Pr

ocedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND

PROTECTIVE CLOTHING.

Unusual Fire/Explosion Hazard:NONE.

======== Accidental Release Measures ==========

Spill Release Procedures:FLUSH TO SEWER WITH LARGE AMOUNT OF WATER.
OTHERWISE, ABSORB SPILL WITH VERMICULITE OR OTHER INERT MATERIAL,
THEN PLACE IN A CONTAINER FOR CHEMICAL WASTE. CLEAN SURFACE
THOROUGHLY TO REMOVE RESIDUAL C ONTAMINATION.

Neutralizing Agent: NOT PROVIDED

and Storage ======== Handling

Handling and Storage Precautions: KEEP CONTAINER CLOSED.

Other Precautions:AVOID BREATHING MIST OR VAPOR. AVOID CONTACT WITH EYES AND PROLONGED OR REPEATED CONTACT WITH SKIN. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING.

===== Exposure Controls/Personal Protection ========

Respiratory Protection: NONE SHOULD BE NEEDED.

Ventilation: GOOD GENERAL VENTILATION (TYPICALLY 10 AIR CHANGES PER HOUR) SHOULD BE USED. VENTILAT

ION RATES SHOULD BE MATCHED TO CONDITIONS.

Protective Gloves:FOR PROLONGED OR REPEATED SKIN CONTACT, IMPERVIOUS GLOVES SHOULD BE WORN.

Eye Protection: WEAR SAFETY GLASSES WITH SIDE SHIELDS (OR GOGGLES).

Other Protective Equipment: EYE BATH, SAFETY SHOWER, WASHING FACILITIES.

Work Hygienic Practices:IT IS A GOOD INDUSTRIAL HYGIENE PRACTICE TO MINIMIZE EYE CONTACT. IT IS A GOOD INDUSTRIAL HYGIENE PRACTICE TO MINIMIZE SKIN CONTACT.

Supplemental Safety and Health

ABBREVIATION: N/A = NO

T APPLICABLE. N/AV = NOT AVAILABLE. N/K = UNKNOWN. N/P = NOT PROVIDED. N/R = NOT RELEVANT. N/D = NOT DETERMINED. N/E = NOT ESTABLISHED.

======== Physical/Chemical Properties ===========

HCC:C2

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:>100.C, 212.F

Melt/Freeze Pt:M.P/F.P Text:NOT PROVIDED Decomp Temp:Decomp Text:NOT PROVIDED

Vapor Pres:68F: 23 MBAR (18 MM HG)

Vapor Density:0.6 Spec Gravity:1.408

pH:10.9

Viscosity: NOT PROVIDED

Evaporation Rate & Dr. Reference: NOT PROV

IDED

Solubility in Water: COMPLETE

Appearance and Odor: COLORLESS, ODORLESS LIQUID.

Percent Volatiles by Volume:55-60 WT

Corrosion Rate: NOT PROVIDED

======== Stability and Reactivity Data ============


Stability Indicator/Materials to Avoid:YES

NONE WITH COMMON MATERIALS AND CONTAMINANTS WITH WHICH THE MATERIAL MAY REASONABLY COME INTO CONTACT.

Stability Condition to Avoid:NOT PROVIDED Hazardous Decomposition Products:NONE

===== Toxicological Information ======

Toxicological Information:INHALATION: EXPECTED TO BE A LOW HAZARD FOR USUAL INDUSTRIAL OR COMMERCIAL HANDLING BY TRAINED PERSONNEL. IN CONTACT WITH STRONG ACIDS OR IF HEATED, SULFITES MAY LIBERATE SULFUR DIOXIDE GAS. SULFUR D IOXIDE GAS IS IRRITATING TO THE RESPIRATORY TRACT. SOME ASTHMATICS OR HYPERSENSITIVE INDIVIDUALS MAY EXPERIENCE DIFFICULT BREATHING. EYES: NO SPECIFIC HAZARD KNOWN. MAY CAUSE TRANSIENT IRRITATION. SKI N: THIS MATERIAL HAS A LOW PO



is information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.