View NSN Online: https://aerobasegroup.gr/nsn/6750-00-153-8909

EASTMAN KODAK COMPANY -- 146 4924, PT B, KODAK DK-50 DEVELOPER (SEE SUPPL) -- 6750-00-153-8909

Product ID:146 4924, PT B, KODAK DK-50 DEVELOPER (SEE SUPPL) MSDS Date:02/24/2001 FSC:6750 NIIN:00-153-8909 Status Code:A Kit Part:Y **MSDS Number: CLHCR** === Responsible Party === Company Name: EASTMAN KODAK COMPANY Address:343 STATE STREET City:ROCHESTER State:NY ZIP:1465 0 Country:US Info Phone Num:716-722-5151 Emergency Phone Num:716-722-5151 Preparer's Name:NOT PROVIDED CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139

Ingred Name:SODIUM SULFITE CAS:7757-83-7 RTECS #:WE2150000 Minumum % Wt:75. Maxumum % Wt:80. Other REC Limits:NOT PROVIDED ACGIH TLV:NOT PROVIDED

Ingred Name:SODIUM METABORATE CAS:7775-19-1 RTECS #:ED4640000 Minumum % Wt:15. Maxumum % Wt:20. Other REC Limits:NOT PROVIDED ACGIH TLV:NOT PROVIDED

Ingred Name:POTASSIUM BROMIDE CAS:7758-02-3 RTECS #:TS7650000 Minumum % Wt:1. Maxumum % Wt:5. Other REC Limits:NOT PROVIDED ACGIH TLV:NOT PROVIDED

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:I

NHALATION: MAY BE HARMFUL IF INHALED.

AIRBORNE DUST IRRITATING. IN CONTACT WITH STRONG ACIDS OR IF HEATED, SULFITES MAY LIBERATE SULFUR DIOXIDE GAS. SULFUR DIOXIDE GAS IS IRRITATING TO RESPIRATORY TRACT. SOME ASTHMATICS OR HYPERSENSITIVE INDIVIDUALS MAY EXPERIENCE DIFFICULT BREATHING. EYES: CAUSES BURNS. AIRBORNE DUST IRRITATING. SKIN: CAUSES IRRITATION. MAY BE ABSORBED IN TOXIC AMOUNTS THROUGH DAMAGED OR ABRADED SKIN. MATERIAL HAS LOW POTENTIAL TO CAUSE ALLERGIC SKIN

REACTIONS; CASES OF HUMAN SKIN SENSITIZATION HAVE BEEN REPORTED. INGESTION: MAY BE HARMFUL IF SWALLOWED. MAY CAUSE BURNS OF GASTROINTESTINAL TRACT IF SWALLOWED.

Explanation of Carcinogenicity:INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC): HYDROQUINONE, GROUP 3; NOT CLASSIFIABLE. - AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS (ACGIH): HYDROQUINONE, A3; CONFIRMED ANIMAL CAR CINOGEN WITH UNKNOWN RELEVANCE TO HUMANS. - NATIONAL TOXICOLOGY PROGRAM ( NTP): NONE -OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA): NONE Effects of Overexposure: INHALATION: AIRBORNE DUST IRRITATING. IN CONTACT WITH STRONG ACIDS OR IF HEATED, SULFITES MAY LIBERATE SULFUR DIOXIDE GAS. SULFUR DIOXIDE GAS IS IRRITATING TO RESPIRATORY TRACT. EYES: CAUSES BURNS. AIRBORNE DUST IRRITATING. SKIN: CAUSES IRRITATION. INGESTION: MAY CAUSE BURNS OF GASTROINTESTINAL TRACT IF SWALLOWED. Medical Cond Aggravated by Exposure:SOME ASTHMATICS, HYPERSENS **ITIVE OR** SULFITE-SENSITIVE INDIVIDUALS MAY EXPERIENCE DIFFICULT BREATHING, WHEEZING, CHEST TIGHTNESS, STOMACH UPSET, HIVES, FAINTNESS, WEAKNESS AND DIARRHEA. First Aid:INHALATION: IF SYMPTOMATIC, MOVE TO FRESH AIR. TREAT SYMPTOMATICALLY. GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EYES: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTEN TION IMMEDIATELY. SKIN: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES WHILE REMOVING CONTAMINATED CLOTHING AND SHOES. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. WASH CONTAMINATED CLOTHI NG BEFORE REUSE. DESTROY OR THOROUGHLY CLEAN CONTAMINATED SHOES. INGESTION: DO NOT INDUCE VOMITING. GIVE VICTIM A GLASS OF WATER. CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY, NEVER GIVE ANYT HING BY MOUTH TO AN UNCONSCIOUS PERSON.

===

Flash Point:NONE Extinguishing Media:USE APPROPRIATE AGENT FOR ADJACENT FIRE. Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING. FIRE OR EXCESSIVE HEAT MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS. Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures: AVOID GENERATION OF DUST. FLUSH TO SEWER WITH LARGE AMOUNT OF WATER. CLEAN SURFACE THOROUGHLY TO REMOVE RESIDUAL

## CONTAMINATION.

Handling and Storage Precautions: KEEP CONTAINER TIGHTLY CLOSED. KEEP AWAY FROM INCOMPATIBLE SUBSTANCES.

Other Precautions: AVOID BREATHING DUST. DO NOT GET IN EYES AND AVOID CONTACT WITH SKIN AND CLOTHING. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING.

Respiratory Protection: IF ENGINEERING CONTROLS DO NOT MAINTAIN A IRBORNE

CONCENTRATIONS BELOW RECOMMENDED EXPOSURE LIMITS, APPROVED RESPIRATOR MUST BE WORN. RESPIRATOR: N95 PARTICULATE FILTER. RESPIRATOR SHOULD BE WORN IF HA ZARDOUS DECOMPOSITION PRODUCTS LIKELY, OR HAVE BEEN RELEASED. RESPIRATOR: ACID GAS. IF RESPIRATORS USED, ASSURE COMPLIANCE WITH OSHA STANDARD 29 CFR 1910.134.

Ventilation: GOOD GENERAL VENTILATION (TYPICALLY 10 AIR CHANGES PER HOUR) SHOULD BE USED. VENTILATION RATES SHOULD BE MATCHED TO CONDITIONS.

Protective G

Ioves:WEAR IMPERVIOUS GLOVES AND PROTECTIVE CLOTHING APPROPRIATE FOR RISK OF EXPOSURE

Eye Protection:WEAR SAFETY GLASSES WITH SIDE SHIELDS (OR GOGGLES) AND A FACE SHIELD.

Other Protective Equipment: EYE BATH, SAFETY SHOWER, WASHING FACILITIES Work Hygienic Practices: NOT PROVIDED

Supplemental Safety and Health

THIS IS A KIT. THE OTHER MSDS SERIAL NUMBER: CLHCQ. USE PROCESS ENCLOSURES, LOCAL EXHAUST VENTILATION, OR OTHER ENGINEERING CONTROLS TO MAINTAIN AIRBORNE LEVELS BELOW RECOMM ENDED EXPOSURE LIMITS.

HCC:T6

NRC/State Lic Num:NOT RELEVANT Melt/Freeze Pt:M.P/F.P Text:NOT AVAILABLE Decomp Temp:Decomp Text:NOT PROVIDED Vapor Pres:NEGLIGIBLE Spec Gravity:>1.00 Viscosity:NOT RELEVANT Evaporation Rate & amp; Reference:NOT RELEVANT Solubility in Water:COMPLETE Appearance and Odor:LIGHT YELLOW SOLID. ODORLESS. Percent Volatiles by Volume:NEGLIGIBLE Corrosion Rate:NOT PROVIDED

======= Stability

Stability Indicator/Materials to Avoid:YES STRONG ACIDS Stability Condition to Avoid:NOT PROVIDED Hazardous Decomposition Products:SULFUR DIOXIDE

Toxicological Information:CONTAINS: SODIUM METABORATE. BASED ON REPEATED-DOSE INGESTION STUDIES IN ANIMALS, MAY CAUSE ADVERSE REPRODUCTIVE AND DEVELOPMENTAL EFFECTS. HOWEVER, THE DOSES ADMINISTERED WERE MANY TIMES TH OSE TO WHI CH HUMANS WOULD NORMALLY BE EXPOSED.

Ecological:THE FOLLOWING PROPERTIES ARE ESTIMATED FROM THE COMPONENTS OF THE PREPARATIONS. POTENTIAL TOXICITY: FISH LC50 MG/L: >100. DAPHNID EC50 MG/L: 10-100. ALGAL IC50 MG/L: NOT AVAILABLE. ORGANICS REA DILY DEGRADABLE (>70%): NOT APPLICABLE. POTENTIAL BIOACCUMULATION: LOG POW 100.

Waste

Disposal Methods:DISCHARGE, TREATMENT, OR DISPOSAL MAY BE SUBJECT TO NATIONAL, STATE, OR LOCAL LAWS. SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE, FOLLOW LABEL WARNINGS EVEN AFTER CONTAINER IS EMPTIED. FLUSH TO SEW ER WITH LARGE AMOUNT OF WATER.

Transport Information:FOR TRANSPORTATION INFORMATION REGARDING THIS PRODUCT CALL THE KODAK WORLDWIDE TRANSPORTATION HAZMAT HOT LINE: (716) 722-2400 BETWEEN

8 A.M. AND 5 P.M. (EASTERN STANDARD TIME), MONDAY THROUGH FR IDAY.

SARA Title III Information:CHEMICAL(S) SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OR TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT (SARA) OF 1986 AND 40 CFR PART 372: NONE. Federal Regulatory Information:NOT PROVIDED

State Regulatory Information:MATERIAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER: N

## ONE - MATERIAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE ADVERSE REPRODUCTIVE EFFECTS: NONE

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.