

SPRAYLAT CORPORATION -- SPRAYLAT SC-1074B-1 -- 8030-01-181-6269

=====
Product Identification
=====

Product ID:SPRAYLAT SC-1074B-1
MSDS Date:06/07/1999
FSC:8030
NIIN:01-181-6269
Status Code:A
MSDS Number: CLKKD
=== Responsible Party ===
Company Name:SPRAYLAT CORPORATION
Address:716 SOUTH COLUMBUS AVENUE
City:MT. VERNON
State:NY
ZIP:10550
Country:US
Info Phone Num:914-699-3030
Emergency Phone Num:(
800)424-9300
Preparer's Name:HENRY SIMMONS
Chemtrec Ind/Phone:(800)424-9300
CAGE:87354

==== Contractor Identification ====
Company Name:SPRAYLAT CORPORATION
Address:716 SOUTH COLUMBUS AVENUE
Box:City:MT. VERNON
State:NY
ZIP:10550
Country:US
Phone:914-699-3030;310-559-2335
CAGE:87354

=====
Composition/Information on Ingredients
=====

Ingred Name:CARBON BLACK
CAS:1333-86-4
RTECS #:FF5800000
= Wt:2.09
OSHA PEL:3.5 MG/M3
ACGIH TLV:3.5 MG/M3

Ingred Name:ZINC CHROMATE
CAS:13530-65-9

RTECS #:GB3290000
= Wt:.35
ACGIH TLV:0.01 MG/M3

=====
Hazards Identification
=====

Effects of Overexposure:SPRAY MIST/VAPORS OF SPRAY PAINTS MAY CAUSE IRRITATION TO THE EYES, NOSE, THROAT, OR OTHER REPRODUCTIVE HARM. THIS PRODUCT IS IRRITATING TO THE MUCOUS MEMBRANES. MAY CAUSE ALLERGIC RESPIRATORY REAC TION. EFFECTS MAY BE PERMANENT. THIS PRODUCT MAY BE HARMFUL IF IT IS SWALLOWED. THIS PRODUCT MAY CAUSE EYE IRRITATION. THIS MATERIAL CONTAINS SUSPECT OR POTENTIAL CARCINOGEN LISTED BY THE AGENCIES OR ORGANIZATIONS. THIS MATERIAL MAY CAUSE IRRITATION, DRYING OR DERMATITIS ON PROLONGED EXPOSURE TO SKIN.

=====
First Aid Measures
=====

First Aid:EYE CONTACT: FLUSH WITH LUKE WARM WATER FOR 15 MINS. SEE PHYSICIAN IMMEDIATELY. SKIN CONTACT: FLUSH WASH WITH COPIOUS AMOUNTS OF LUKE WARM WATER. REMOVE CONTAMINATED CLOTHING PROMPTLY. CONTACT A PHYS ICIAN IMMEDIATELY. INHALATION:REMOVE EXPOS ED INDIVIDUAL TO FRESH AIR. RESTORE BREATHING IF REQUIRED. CONTACT A PHYSICIAN IMMEDIATELY. INGESTION: RINSE MOUTH IMMEDIATELY. GIVE EXPOSED INDIVIDUAL 6 T O 8 OUNCES OF LIQUID. (NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.) DO NOT INDUCE VOMITING UNLESS ADVISED A PHYSICIAN IMMEDIATELY

=====
Fire Fighting Measures
=====

Extinguishing Media:USE CARBON DIOXIDE, DRY CHEMICALS, OR FOAM.
Fire Fighting Procedures:CLEAR FIRE AREA OF UNPROTECTED

PERSONNEL. DO

NOT ENTER CONFINED SPACE WITHOUT PERMISSION. FIGHT FIRES WEARING OSHA APPROVED HELMET, FACE SHIELD, GLOVES, HOOD AND SELF CONTAINED BREATHING APPARATUS. FIGHT FIRE FROM A SAFE DISTANCE OR A PROTECTED LOCATION.

===== Accidental Release Measures =====

Spill Release Procedures: STAY UPWIND AND AWAY FROM SPILL UNLESS WEARING APPROPRIATE PROTECTIVE EQUIPMENT. STOP AND/OR CONTAIN DISCHARGE IF IT CAN BE DONE SAFELY. KEEP ALL SOURCES OF IGNITION AWAY. VENTILATE AREA OF SPILL. USE NON-SPARKING TOOLS FOR CLEANUP. COVER WITH INERT MATERIAL TO REDUCE FUMES. KEEP OUT OF DRAINS, SEWERS, OR WATERWAYS. CONTACT FIRE AUTHORITIES. NOTIFY LOCAL HEALTH AND POLLUTION CONTROL AGENCIES.

===== Handling and Storage =====

Handling and Storage Precautions: IF FLAMMABLE, KEEP CONTAINERS COOL, DRY, AND AWAY FROM SOURCES OF IGNITION. STORE THIS PRODUCT WITH ADEQUATE VENTILATION. DO NOT SMOKE IN STORAGE AREAS. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: USE DUST MASK OR RESPIRATOR IF THE CONCENTRATION IS HIGH.
Ventilation: THE VENTILATION AS REQUIRED TO CONTROL VAPOR/DUST/MIST CONCENTRATION. AVOID PROLONGED OR REPEATED BREATHING OF VAPORS.
Protective Gloves: WEAR RESISTANT GLOVES SUCH AS NATURAL RUBBER, NEOPRENE, BUTYL OR NITRILE.
Eye Protection: USE SAFETY EYEWEAR WITH PERFORATED SIDESHIELDS OR GOGGLES
Work Hygienic Practices: WASH HANDS THOROUGHLY BEFORE EATING AND USING WASHROOM, REMOVE CONTAMINATED CLOTHING IMMEDIATELY AND DO NOT REUSE UNTIL IT HAS BEEN PROPERLY LAUNDERED.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt: =93.3C, 200.F
B.P. Text: 200-300F
Solubility in Water: MISCIBLE
Appearance and Odor

r:BLACK FLUID AND MILD ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

THIS PRODUCT IS INCOMPATIBLE WITH STRONG OXIDIZERS; MAY CAUSE FIRE OR EXPLOSIONS ON CONTACT.

Stability Condition to Avoid: AVOID EXPOSURE TO SPARKS, OPEN FLAME, HOT SURFACES, AND ALL SOURCES OF HEAT AND IGNITION.

Hazardous Decomposition Products: IN THE PRESENCE OF AIR MAY YIELD CARBON MONOXIDE AND/OR CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF PRODUCTS IN ACCORDANCE WITH APPLICABLE LOCAL, COUNTY, STATE, AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.