View NSN Online: https://aerobasegroup.gr/nsn/5930-01-366-0049

Product ID: POLYTHIOETHER POLYMER COMPOUND PR1829 B-1/2 - BASE COMPOUND MSDS Date:09/03/1998 FSC:8030 NIIN:01-366-0049 Status Code:A MSDS Number: CLKMC === Responsible Party === Company Name: PRC-DESOTO INTERNATIONAL, INC. A PPG I NDUSTRIES COMPANY Address:5430 SAN FERNANDO RD Box:1800 City:GLENDALE State:CA ZIP:91209 Country:US Info Phone Num:818-240-2060 Emergency Phone Num: (800) 424-9300 Preparer's Name: HENRY SIMMONS Chemtrec Ind/Phone:(800)424-9300 CAGE:83574 === Contractor Identification === Company Name: PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY Address:5430 SAN FERNANDO RD Box:1800 City:GLENDALE State:CA ZIP:91209 Country:US Phone:818-240-2060 CAGE:83574 ======== Composition/Information on Ingred ients =========== Ingred Name: TITANIUM DIOXIDE CAS:13463-67-7 RTECS #:XR2275000 < Wt:5. OSHA PEL:15 MG/M3 ACGIH TLV:10 MG/M3 Ingred Name:CALCIUM CARBONATE @ LIMESTONE CAS:1317-65-3 RTECS #:EV9580000 = Wt:25. OSHA PEL:15 MG/M3 ACGIH TLV:10 MG/M3 Ingred Name:2-ETHOXYETHANOL CAS:110-80-5 RTECS #:KK8050000 < Wt:5.

OSHA PEL:740 MG/M3:200 PPM

VATIVES CAS:67762-90-7

Ingred Name:ALUMINUM HYDROXIDE CAS:21645-51-2 RTECS #:BD0940000

ETHYLENE GLYCOL MONOETHYL ETHER EYES: MAY CAUSE BURNING, TEARING,
REDDENING, POSSIBLE TRANSIENT CORNEAL INJURY. INH ALATION: MAY CAUSE NASAL AND
RESPIRATORY
RRITATION. INGESTION: MAY CAUSE NAUSEA, VOMITING, ABDOMINAL DISCOMFORT AND
DIARRHEA. CERTAIN GLYCOL ETHERS HAVE BEEN FOUND TO CAUSE BIRTH DEFECTS AND DAMAGE
TICLES IN LABORATORY ANIMALS. THIS CHEMICAL IS ON THE LIST ENTITLED
CHEMICAL KNOWN BY THE STATE OF CALIFORNIA TO CAUSE REPRODUCTIVE TOXICITY.
======================================
First Aid:EYES: FLUSH WITH WARM WATER FOR 15 MINUTES. IF SYMPTOMS PERSISTS, CONSULT A PHYSICIAN.
SKIN: WASH WITH SOAP AND WATER. IF SYMPTOMS PERSISTS, CONSULT A PHYSICIAN. INHALATION:REMOVE TO FRESH AIR. IF SYMPTOMS ARE PRESENT, CONSULT A PHYSICIAN INGESTION: CONSUL
ΓΑ
PHYSICIAN.
======================================
Flash Point:>93.3C, 200.F
Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER.
Fire Fighting Procedures:USE AIR SUPPLIED RESPIRATOR. USE WATER TO COOL HEAT EXPOSED CONTAINERS.
Jnusual Fire/Explosion Hazard: HIGH TEMPERATURE MAY CAUSE PRESSURE BUILDUP IN CLOSED CONTAINERS

Spill Release Procedures: SCOOP INTO CONTAINERS. CLEAN

## -UP RESIDUE WITH A SUITABLE SOLVENT.

Handling and Storage Precautions: WASH THOROUGHLY AFTER HANDLING AND BEFORE SMOKING OR EATING. AVOID INGESTION.

Respiratory Protection:NONE Ventilation:GENERAL VENTILATION. Protective Gloves:SOLVENT RESISTANT GLOVES. Eye Protection:SAFETY GLASSES. Other Protective Equipment:NONE KNOWN Supplemental Safety and Health

Vapor Density:>AIR Spec Gravity:1.43 VOC Pounds/Gallon:18 Evaporation Rate & amp; Reference:NON VOLATILE Appearance and Odor:WHITE THIXOTROPIC PASTE Percent Volatiles by Volume:0

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid:NOT KNOWN Hazardous Decomposition Products:OXIDES OF CARBON , SULFUR DIOXIDE, TR ACES OF HYDROGEN SULFIDE

Waste Disposal Methods:NOT A HAZARDOUS WASTE ACCORDING TO EPA REGULATIONS. CONSULT STATE REGULATIONS PRIOR TO DISPOSAL TO DISPOSAL OF SPILLAGE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this informati on to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.