

DEFT, INC. -- POLYURETHANE 1-COAT, TT-P-2756, 35109 -- 8010-01-376-3707

===== Product Identification =====

Product ID:POLYURETHANE 1-COAT, TT-P-2756, 35109

MSDS Date:05/30/2000

FSC:8010

NIIN:01-376-3707

Status Code:A

MSDS Number: CLKSK

=== Responsible Party ===

Company Name:DEFT, INC.

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92614

Country:US

Info Phone Num:949-474-0400

Emergency Pho

ne Num:800-424-9300

Preparer's Name:RYAN MICKELSON

CAGE:33461

=== Contractor Identification ===

Company Name:DEFT, INC.

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92614

Country:US

Phone:949-474-0400

CAGE:33461

===== Composition/Information on Ingredients =====

Ingred Name:N-BUTYL ACETATE

CAS:123-86-4

RTECS #:AF7350000

= Wt:20.

OSHA PEL:710 MG/M3;150 PPM

ACGIH TLV:713 MG/M3;150 PPM

ACGIH STEL:950 MG/M3;200 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:

ETHYL 3-ETHOXYPROPIONATE

CAS:763-69-9

RTECS #:UF3325000

< Wt:5.

Ingred Name:DISPERSION AID

< Wt:1.

Ingred Name:XYLENE

CAS:1330-20-7

RTECS #:ZE2100000

< Wt:1.

ACGIH TLV:434 MG/M3;100 PPM

ACGIH STEL:651 MG/M3;150 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ETHYLBENZENE

CAS:100-41-4

RTECS #:DA0700000

< Wt:.1

OSHA PEL:435 MG/M3;100 PPM

ACGIH TLV:434 MG/M3;100 PPM

ACGIH STEL:543 MG/M3;125 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ISOBUTYL ALCOHOL

CAS:78-8

3-1

RTECS #:NP9625000

< Wt:.1

OSHA PEL:300 MG/M3;100 PPM

ACGIH TLV:152 MG/M3;50 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ANTI-FLOAT AGENT

CAS:1317-65-3

Code:F

RTECS #:EV9580000

< Wt:1.

OSHA PEL:15 MG/M3

ACGIH TLV:10 MG/M3

Ingred Name:METHYL N-AMYL KETONE

CAS:110-43-0

RTECS #:MJ5075000

= Wt:5.

OSHA PEL:465 MG/M3;100 PPM

ACGIH TLV:233 MG/M3;50 PPM

Ingred Name:ANTI MAR AGENT

CAS:9038-95-3

Code:F

RTECS #:MO0911000

< Wt:.1

Ingred Name:ANTI MAR AGENT

me:FLOW AGENT
CAS:26376-86-3
Code:F
< Wt:1.

Ingred Name:DIBUTYLTIN DILAURATE
CAS:77-58-7
RTECS #:WH7000000
< Wt:.1

Ingred Name:2,4-PENTANEDIONE
CAS:123-54-6
RTECS #:SA1925000
< Wt:5.

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: VAPORS ARE IRRITATING TO EYES,
NOSE, AND THROAT. INHALATION MAY CAUSE HEADACHES,
DIFFICULT
BREATHING AND LOSS OF CONSCIOUSNESS. CHRONIC: PROLONGED CONTACT
WILL CAUSE DRYING AND CRACKING OF T HE SKIN, DUE TO DEFATTING
ACTION. SKIN SENSITIZATION, ASTHMA OR OTHER ALLERGIC RESPONSES MAY
DEVELOP.
Effects of Overexposure:INHALATION: IRRITATION OF THE RESPIRATORY TRACT
AND ACUTE NERVOUS SYSTEM DEPRESSION CHARECTERIZED BY THE FOLLOWING
PROGRESSIVE STEPS: HEADACHE, DIZZINESS, STAGGERING GAIT, CONFUSION,
UNCONSCIOUSNESS O R COMA. SKIN AND EYE CONTACT: SK
IN: CONTACT WITH
THE SKIN CAN CAUSE IRRITATION. SYMPTOMS MAY BE SWELLING, REDNESS,
AND RASH. EYES: LIQUID, AERESOLS, OR VAPORS ARE IRRITATING AND
MAY CAUSE TEARING, REDNESS, AND SWELLING ACCOMPANIED BY A STINGING
SENSATION. SKIN ABSORPTION: PROLONGED OR REPEATED CONTACT CAN
CAUSE MODERATE IRRITATION, DRYING, AND DEFATTING OF THE SKIN WHICH
CAN CAUSE THE SKIN TO CRACK. INGESTION: ACUTE: CAN RESULT IN
Medical Cond Aggravated by Exposure:ASTHMA AND ANY OTHER RESPIRATORY

DISORDERS. SKIN ALLERGIES, ECZEMA, AND DERMATITIS.

===== First Aid Measures =====

First Aid:INHALATION: MOVE TO AN AREA FREE FROM RISK OF FURTHER
EXPOSURE. RESTORE BREAHTING. ASTHMATIC TYPE SYMPTOMS MAY DEVELOP
AND MAY BE IMMEDIATE OR DELAYED BY SEVERAL HOURS. OBTAIN MEDICAL
ATTENTION. SKI N: REMOVE CONTIMINATED CLOTHING. WASH AFFECTED
AREAS THOROUGHLY WITH SOAP AND WATER WASH CONTAMINATED CLOTHING
THOROUGHLY BEFORE REUSE EYES: FLU

SH WITH CLEAN LUKEWARM WATER
(LOW PRESSURE) FOR AT LEA ST 15 MINUTES, OCCASIONALLY LIFTING
EYELIDS. OBTAIN MEDICAL ATTENTION. INGESTION: DO NOT INDUCE
VOMINTING. DO NOT GIVE ANYTHING TO AN UNCONCIOUS PERSON. OBTAIN
MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:=19.4C, 67.F

Lower Limits:3.00%

Upper Limits:11.40%

Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG,
WATER SPRAY

Fire

Fighting Procedures:FULL FIRE FIGHTING EQUIPMENT WITH
SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING
SHOULD BE WORN BY FIRE FIGHTERS WATER MAY BE USED TO COOL CLOSED
CONTAINERS TO PREVENT PRESSURE BUILD- UP, AUTO IGNITION OR
EXPLOSION.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE
FROM HEAT, SPARKS, ELECTRICAL EQUIPMENT AND OPEN FLAME. CLOSED
CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. APPLICATION TO
HOT SURFACES REQUI

RES SPECIAL PRECAUTIONS. DURING EMERGENCY
CONDITIONS OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A
HEALTH HAZARD. SYMPTOMS MAY

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE ALL NON-ESSENTIAL PERSONNEL. REMOVE
ALL SOURCES OF IGNITION (FLAME, SPARK SOURCES, HOT SURFACES).
VENTILATE AREA CONTAIN AND REMOVE WITH INERT ABSORBENT AND
NON-SPARKING TOOLS.

===== Handling and Storage =====

==

Handling and Storage Precautions:STORE IN BUILDINGS DESIGNED TO COMPLY
WITH OSHA 1910.106 AVOID STORING NEAR HIGH TEMPERATURES, FIRE ,
OPEN FLAMES, AND SPARK SOURCES. STORE IN TIGHTLY CLOSED CONTAINERS.
STORE IN WELL VENTILATED AREAS .

Other Precautions:KEEP CONTAINERS TIGHT AND UPRIGHT TO PREVENT LEAKAGE.
PREVENT PROLONGED BREATHING OF VAPORS OR SPRAY MISTS. PROLONGED
OVEREXPOSURE MAY CAUSE AN ALLERGIC REACTION. AVOID CONTACT WITH
SKIN AND EYES. DO NOT TAKE INTERNAL

LY. DO NOT HANDLE UNTIL THE
MANUFACTURERS SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD.
WASH HANDS

===== Exposure Controls/Personal Protection =====

Respiratory Protection: A RESPIRATOR THAT IS RECOMMENDED OR APPROVED FOR
USE IN AN ORGANIC VAPOR ENVIRONMENT (AIR PURIFYING OR FRESH AIR
SUPPLIED) IS NECESSARY. OBSERVE OSHA REGULATIONS FOR RESPIRATOR
USE. VENTILATION SHOULD BE PROVIDED TO KEEP EXPOSURE LEVELS BELOW
THE IF TLV LIMITS CAN BE MAINTAINED AND

DOCUMENTED BELOW THE

OSHA/ACGIH LIMITS, AN AIR SUPPLIED RESPIRATOR MAY NOT BE RE

Ventilation: EXHAUST VENTILATION SUFFICIENT TO KEEP THE AIRBORNE
CONCENTRATIONS OF SOLVENT VAPORS OR MISTS BELOW THEIR RESPECTIVE
TLV'S MUST BE UTILIZED

Protective Gloves: COTTON, NEOPRENE, RUBBER POLYETHYLENE

Eye Protection: SPLASH GUARDS OR SIDE SHIELDS, CHEMICAL GOGGLES OR FACE
SHIELDS.

Other Protective Equipment: THE USE OF LONG SLEEVE AND LONG LEG CLOTHING
IS RECOMMENDED. REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt: B.P. Text: 326-401 DEG F

Spec Gravity: 1.2569

Evaporation Rate & Reference: 0.67 X N-BUTYL ACETATE

Solubility in Water: INSOLUBLE

Appearance and Odor: BLUE LIQUID WITH SOLVENT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid: HIGH TEMPERATURES, SPARKS, OR OPEN FLAMES

Hazardous Decomposition Products: BY HIGH HEAT/TEMPERATURES: CARBON
MONOXIDE, CARBON DIOXIDE, AND OXIDES OF NITROGEN.

===== Disposal Considerations =====

Waste Disposal Methods: WASTE MUST BE DISPOSED OF IN ACCORDANCE WITH
FEDERAL, STATE, AND LOCAL ENVIRONMENTAL CONTROL REGULATIONS. EMPTY
CONTAINERS MUST BE HANDLED WITH CARE, DUE TO PRODUCT RESIDUE AND
FLAMMABLE VAPOR DO NOT INCINERATE CLOSED CONTAINERS.

=====

=====
Regulatory Information
=====

SARA Title III Information:THIS PRODUCT CONTAINS THE FOLLOWING TOXIC
CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF
THE EMERGENCY PLANNING AND COMMUNITY RIGHT TO KNOW ACT OF 1986 AND
40 CFR 372: 1330-20-7 XYL ENE, 100-41-4 ETHYL BENZENE

State Regulatory Information:

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of

Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.