

FARWEST PAINT MANUFACTURING CO -- GREEN EPOXY POLYAMIDE PRIMER, FOMULA 150
COMPONENT A -- 8010-00-582-4667

===== Product Identification =====

Product ID:GREEN EPOXY POLYAMIDE PRIMER, FOMULA 150 COMPONENT A

MSDS Date:07/01/1992

FSC:8010

NIIN:00-582-4667

Status Code:A

MSDS Number: CLNNP

=== Responsible Party ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

City:TUKWILA

Sta

te:WA

ZIP:98168

Country:US

Info Phone Num:206-244-8844

Emergency Phone Num:800-424-9300

Preparer's Name:ERNEST CARTER

CAGE:6F266

=== Contractor Identification ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

Box:City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:6F266

===== Composition/Information on Ingredients =====

Ingred Name:N-BUTYL ALCOHOL

CAS:71-36-3

RTECS #:EO1400000

= Wt:25.7

OSHA PEL:300 MG/M3;100 PPM

ACGIH STEL:C152 MG/M3;

C50 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Effects of Overexposure:SKIN: THIS MATERIAL MAY CAUSE IRRITATION, SENSITIZATION, OR DEFATTING OF SKIN UPON PROLONGED OR REPEATED CONTACT. INHALATION: EXCESSIVE EXPOSURE TO VAPORS OR SPRAY MIST CAN RESULT IN HEADACHE, DIZZINE SS, NAUSEA AND LOSS OF CONSCIOUSNESS. SOME REPORTS HAVE ASSOCIATED REPEATED & PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. EYES: THIS MATERIAL MAY BE A N EYE IRRITANT.
Medical Cond Aggravated by Exposure:NONE, WHEN USED IN ACCORDANCE WITH SAFE HANDLING INSTRUCTIONS, (SEE SECTION VIII).

===== First Aid Measures =====

First Aid:SKIN: PROMPTLY WASH WITH SOAP AND WATER. REMOVE AND WASH ANY CONTAMINATED CLOTHING BEFORE REUSE.EYES: FLUSH WITH LARGE QUANTITIES OF WATER FOR 15 MINUTES AND SEEK MEDICAL ATTENTION.SWALLOWING:IF INGESTED DO NOT INDUCE VOMITING; KEEP PERSON WARM AND QUIET AND GET MEDICAL ATTENTION. ASPIRATION OF MATERIAL INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. INHALATION: REMOVE VICTIM TO FRESH AIR IMMEDIATELY. IF RESPIRATORY SYMPTOMS DEVELOP, SEEK MEDICAL ATTENTION AT ONCE.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:=-36.1C, 97.F
Lower Limits:1.4%
Upper Limits:10.9%
Extinguishing Media:FOAM, CO2, DRY CHEMICAL, OR

WATER FOG. WATER MAY BE
UNSUITABLE AS EXTINGUISHING AGENT BUT CAN BE USED TO KEEP
CONTAINERS COOL.

Fire Fighting Procedures:FIREFIGHTERS AND OTHERS EXPOSED TO VAPORS OR
PRODUCTS OF COMBUSTION SHOULD WEAR SELF CONTAINED BREATHING
APPARATUS.EVACUATE AREA OF UNPROTECTED PERSONNEL. WEAR PROTECTIVE
CLOTHING.

Unusual Fire/Explosion Hazard:VAPORS MAY FORM AN EXPLOSIVE MIXTURE IN
AIR AND MAY BE IGNITED BY SPARKS, PILOT LIGHTS, ETC. CLOSED
CONTAINERS MAY RUPTURE WHEN EXPOSED
TO EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE
AREA. ABSORB SPILL WITH AN ABSORBENT
MATERIAL SUCH AS SAWDUST, VERMICULITE OR SAND AND PLACE MATERIAL INTO A
CLOSED
CONTAINER. IF LARGE SPILL, DIKE AREA TO PR EVENT THIS MATERIAL FROM
ENTERING WATER
SYMPTOMS OR SEWERS. WEAR PROTECTIVE EQUIPMENT DURING CLEANUP.

===== Handling and Storage =====

Han
dling and Storage Precautions:AVOID PROLONGED OR REPEATED INHALATION
OF HEATED VAPORS OR SPRAY MIST. KEEP AWAY
FROM HEAT OR OPEN FLAME. THIS MATERIAL NAY CAUSE SENSITIZATION. DO NOT
GET IN EYES,
ON SKIN OR CLOTHING. DO NOT ALLOW CONTAMINATED CLOTHING TO CONTACT
SKIN. DO NOT
WELD ON FULL OR EMPTY CONTAINERS. KEEP CONTAINERS CLOS
Other Precautions:THIS MATERIAL HAS BEEN CATEGORIZED AS HAVING THE
FOLLOWING HAZARD(S) AS DEFINED BY
SARA TITLE III REGULATIONS (40 CFR 370): ACUTE, FIRE
THE INFORMATION IN
THIS DATA SHEET IS
BELIEVED TO BE ACCURATE A ND TRUE AT THE TIME OF PREPARATION OF THIS
DOCUMENT. THIS
IS NOT WARRANTY OF PRODUCT OR PRODUCT SPEC IFICATION. THE END-U

===== Exposure Controls/Personal Protection =====

Respiratory Protection:A CANISTER TYPE RESPIRATOR MUST BE WORN TO
PREVENT THE INHALATION OF VAPORS OR SPRAY MIST WHEN THE TLV OR PEL
IS EXCEEDED.
Ventilation:GENERAL VENTILATION IS REQUIRED DURING NORMAL USE. LOCAL
VENTILATI

ON MAY BE REQUIRED DURING CERTAIN OPERATIONS TO KEEP
EXPOSURE LEVEL BELOW THE LIMITS.

Protective Gloves:CHEMICAL RESISTANT NITRILE, NEOPRENE OR RUBBER GLOVES
REQUIRED.

Eye Protection:WEAR FACE SHIELD OR CHEMICAL GOGGLES.

Other Protective Equipment:WEAR PROTECTIVE CLOTHING TO PREVENT SKIN
CONTACT.EYE WASH STATION AND SAFETY SHOWER SHOULD BE AVAILABLE.

Work Hygienic Practices:WASH HANDS BEFORE EATING OR SMOKING.

Supplemental Safety and Health

===== Physical/Chemical Prop
erties =====

Boiling Pt:B.P. Text:243-245 F.

Vapor Pres:4.39MMHG@20 C

Vapor Density:HEAVIER

VOC Pounds/Gallon:368

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:NO

Appearance and Odor:GREEN SOLUTION WITH MILD ODOR

Percent Volatiles by Volume:47.43%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG OXIDANTS, ACIDS, BASES AND EPOXY HARDENERS
UNDER UNCONTROLLED CONDITI
ONS.

Stability Condition to Avoid:HEAT, SPARKS & OPEN FLAME. IF PRODUCT
CONTAINS ALUMINUM, MOISTURE IN CLOSED CONTAINERS WILL GENERATE
HYDROGEN GAS.

Hazardous Decomposition Products:INCOMPLETE COMBUSTION CAN YIELD CARBON
MONOXIDE AND TOXIC VAPORS.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:IF DISCARDED, THE MATERIAL AND CONTAINERS SHOULD
BE TREATED AS HAZARDOUS WASTE
BASED ON THE

CHARACTERISTICS OF IGNITABILITY AS DEFINED UNDER FEDERAL
RCRA
REGULATIONS (40 CFR 261). DISPOSAL OF THIS MATERIAL OR ITS CONTAINERS
REQUIRES
COMPLIANCE WITH APPLICABLE LABELING, PACKAGING AND RECORDKEEPING STANDARDS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.