

POLYMERIC SYSTEMS, INC. -- PSI-601 SILICONE SEALANT -- 8040-00-843-0802

=====
Product Identification
=====

Product ID:PSI-601 SILICONE SEALANT
MSDS Date:04/02/1997
FSC:8040
NIIN:00-843-0802
Status Code:A
Kit Part:Y
MSDS Number: CLQML
=== Responsible Party ===
Company Name:POLYMERIC SYSTEMS, INC.
Address:723 WHEATLAND STREET
City:PHOENIXVILLE
State:PA
ZIP:19460
Country:US
Info Phone Num:215-935-1170
70
Emergency Phone Num:215-935-1170
Preparer's Name:DAVID CROSSAN
CAGE:0KND3
=== Contractor Identification ===
Company Name:POLYMERIC SYSTEMS, INC.
Address:723 WHEATLAND STREET
Box:City:PHOENIXVILLE
State:PA
ZIP:19460
Country:US
Phone:610-935-1170
CAGE:0KND3

=====
Composition/Information on Ingredients
=====

Ingred Name:DIHYDROXPOLYDIMETHYLSILOXANE
CAS:70131-67-8
Other REC Limits:NONE RECOMMENDED

Ingred Name:POLYDIMETHYLSILOXANE FLUID
CAS:63148-62-9
Other REC Limits:NONE RE

COMMENDED

Ingred Name:AMORPHOUS SILICA, FUMED
CAS:112945-52-5
RTECS #:VV7310000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:80 MG/M3

Ingred Name:METHYLTRACETOXYSILANE
CAS:4253-34-3
RTECS #:VV4500000
Fraction by Wt: 2-6%
Other REC Limits:NONE SPECIFIED

Ingred Name:ETHYLTRACETOXYSILANE
CAS:17689-77-9
Fraction by Wt: 2-6%
Other REC Limits:NONE SPECIFIED

Ingred Name:VOC: 0.4 LBS/GAL
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: SEVERE IRRITATION TO
RESPIRATORY TRACT, PULMONARY EDEMA, EYE LACRIMATION, CORNEAL EDEMA,
SKIN IRRITATION AND DERMATITIS. CHRONIC: BRONCHITIS, LARYNGITIS;
DERMATITIS, CONJUNCTIVITIS.
Medical Cond Aggravated by Exposure:RESPIRATORY, SKIN, OR EYE DISEASES.

=====
===== First Aid Measures =====
=====

First
Aid:REMOVE TO FRESH AIR. WASH SKIN WITH SOAP AND WATER. FLUSH
EYES WITH WATER FOR AT LEAST 15 MINUTES.

=====
===== Fire Fighting Measures =====
=====

Flash Point Method:CC
Flash Point:>400F,>204C
Lower Limits:NA
Upper Limits:NA
Extinguishing Media:WATER SPRAY, CO2, DRY CHEMICALS, FOAM, SAND
Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS
OPERATED IN A POSITIVE PRESSURE MODE.
Unusual Fire/Explosion Hazard:TOXIC GASES AND AEROSOLS MAY BE PRODUCED

BY COMBUSTION, E.G. CO AND SIO2.

===== Accidental Release Measures =====

Spill Release Procedures:MATERIAL RELEASES ACETIC ACID ON EXPOSURE TO AIR. PROVIDE ADEQUATE VENT DURING CLEAN UP. WEAR PROPER PROTECTIVE EQUIPMENT IF HANDLING LARGE AMOUNTS. TRANSFER TO A WASTE CONTAINER. LET CURE TO SOLID RUBBER, ALLOWING LIBERATED ACETIC ACID TODISSIPATE.

Neutralizing Agent:AQUEOUS SODIUM BICARBONATE

===== Handling and Storage =====
=====

Handling and Storage Precautions:AVOID PROLONGED SKIN CONTACT. LIBERATED ACETIC ACID VAPORS CAUSE IRRITATION TO SKIN, EYES, AND BRONCHIAL TISSUE. DO NOT INGEST.

Other Precautions:WASH BEFORE EATING, DRINKING, OR SMOKING. DO NOT RUB EYES WHILE WORKING WITH SEALANT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF USED IN A CLOSED SPACE WHERE VENTILATION IS INADEQUATE, USE A CHEMICAL CARTRIDGE RESPIRATOR WITH FULL FACE

PIECE AND ORGANIC VAPOR CARTRIDGE(S) (MSHA/NIOSH APPROVED) TO PROTECT AGAINST ACETIC ACID VAPORS.

Ventilation:RECOMMENDED 10 COMPLETE AIR CHANGES PER HOUR.

Protective Gloves:DISPOSABLE PLASTIC

Eye Protection:SAFETY GLASSES

Other Protective Equipment:NONE

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:NA

Melt/Freeze Pt:M.P/F.P Text:NA

Decomp Temp:Decomp Text:>400F,>204C

Vapor Pres: